



# Magnitude Simba Amazon Athena JDBC Data Connector

---

## Migration Guide

Version 2.1.1

July 2023

## Copyright

This document was released in July 2023.

Copyright ©2014-2023 Magnitude Software, Inc., an insightsoftware company. All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from Magnitude, Inc.

The information in this document is subject to change without notice. Magnitude, Inc. strives to keep this information accurate but does not warrant that this document is error-free.

Any Magnitude product described herein is licensed exclusively subject to the conditions set forth in your Magnitude license agreement.

Simba, the Simba logo, SimbaEngine, and Simba Technologies are registered trademarks of Simba Technologies Inc. in Canada, the United States and/or other countries. All other trademarks and/or servicemarks are the property of their respective owners.

All other company and product names mentioned herein are used for identification purposes only and may be trademarks or registered trademarks of their respective owners.

Information about the third-party products is contained in a third-party-licenses.txt file that is packaged with the software.

## Contact Us

Magnitude Software, Inc.

[www.magnitude.com](http://www.magnitude.com)

## About This Guide

### Purpose

This document lists differences between the connectors that may disrupt workflows when you migrate from the 1.x connector to the 2.x connector, and provides recommendations on how to recreate those workflows for a successful migration.

### Audience

The guide is intended for end users of the Simba Amazon Athena JDBC Connector.

### Document Conventions

*Italics* are used when referring to book and document titles.

**Bold** is used in procedures for graphical user interface elements that a user clicks and text that a user types.

`Monospace font` indicates commands, source code or contents of text files.

#### Note:

A text box with a pencil icon indicates a short note appended to a paragraph.

#### Important:

A text box with an exclamation mark indicates an important comment related to the preceding paragraph.

## Contents

Upgrading From 1.x to 2.0.x .....	5
JDBC Connector Class Name .....	5
Connection URL .....	5
Connector Configuration Options .....	6
ResultSetMetaData Differences for API Calls .....	7
Data Type for TIME Literal in Query Result .....	10
Upgrading from 2.0.2 to 2.0.5 or later .....	11
Result Set Streaming Support .....	11

## Upgrading From 1.x to 2.0.x

### JDBC Connector Class Name

The connectors use different class names.

Version 1.x	Version 2.x
<code>com.simba.athena.amazonaws.athena.jdbc.AthenaDriver</code>	<code>com.simba.athena.jdbc.Driver</code>

If you are using the following line in your code to explicitly load the connector class in your source code:

```
Class.forName
```

```
("com.simba.athena.amazonaws.athena.jdbc.AthenaDriver");
```

then you will need to change it to:

```
Class.forName("com.simba.athena.jdbc.Driver");
```

### Connection URL

#### Specifying the Host and Port

The 2.x version provides an alternative way to specify the AWS region.

1.x Version	2.x Version
<code>jdbc:awsathena://athena.{REGION}.amazonaws.com:443</code>	<code>jdbc:awsathena://athena.{REGION}.amazonaws.com:443</code> Or <code>jdbc:awsathena://AwsRegion={REGION}</code>
Where {REGION} is a region identifier, such as <code>us-west-2</code>	Where {REGION} is a region identifier, such as <code>us-west-2</code> . If {REGION} is specified using both endpoint URL and <code>AwsRegion</code> , the value specified in <code>AwsRegion</code> takes precedence.

Changes are not required in this case, but be aware the 2.x version provides an alternative way to specify the AWS region in the connection URL.

## Connection String Attributes Separator

The connectors use different attribute separators in their connection URLs.

1.x Version	2.x Version
& and ?	;

The following is an example connection URL using the 1.x version syntax:

```
jdbc:awsathena://athena.us-west-1.amazonaws.com:443?s3_
staging_dir=s3://query-resultsbucket/folder/&query_results_
encryption_option=SSE_S3
```

The following shows the equivalent URL constructed using the 2.x version syntax:

```
jdbc:awsathena://athena.us-west-1.amazonaws.com:443;s3_
staging_dir=s3://query-resultsbucket/folder/;query_results_
encryption_option=SSE_S3
```

## Connector Configuration Options

There are some differences in the supported connection properties for the connectors.

Version 1.x Option	Version 2.x Option	Possible Values	
log_path	LogPath	No difference.	
log_level	LogLevel	1.x	2.x
		OFF	0
		FATAL	1
		ERROR	2
		WARNING	3
		INFO	4
		DEBUG	5
		TRACE	6
retry_base_delay	Not configurable.		

Version 1.x Option	Version 2.x Option	Possible Values
retry_max_backoff_time	Not configurable.	

The following is an example connection URL for enabling logging using the syntax for version 1.x:

```
jdbc:awsathena://athena.us-west-1.amazonaws.com:443?s3_
staging_dir=s3://query-resultsbucket/folder/&log_
level=TRACE&log_path=/tmp
```

The following is the equivalent connection URL using the syntax for version 2.x:

```
jdbc:awsathena://athena.us-west-1.amazonaws.com:443;s3_
staging_dir=s3://query-
resultsbucket/folder/;LogLevel=6;LogPath=/tmp
```

## ResultSetMetaData Differences for API Calls

The connectors return different metadata for the following API calls.

### getCatalogs

Column Name	Version 1.x		Version 2.x	
TABLE_CAT	Metadata	Value	Metadata	Value
	Type Name	varchar	Type Name	VARCHAR
	Type ID	-16	Type ID	12
	Display Size	1073741824	Display Size	128
	Precision	1073741824	Precision	128
	Scale	0	Scale	0

## getColumns

Column Name	Version 1.x		Version 2.x	
TABLE_CAT TABLE_SCHEM TABLE_NAME COLUMN_NAME TYPE_NAME IS_ AUTOINCREMENT IS_ GENERATEDCOLUMN	Metadata	Value	Metadata	Value
	Type Name	varchar	Type Name	VARCHAR
	Type ID	-16	Type ID	12
	Display Size	1073741824	Display Size	128
	Precision	1073741824	Precision	128
	Scale	0	Scale	0
REMARKS COLUMN_DEF IS_NULLABLE SCOPE_CATALOG SCOPE_SCHEMA SCOPE_TABLE	Metadata	Value	Metadata	Value
	Type Name	varchar	Type Name	VARCHAR
	Type ID	-16	Type ID	12
	Display Size	1073741824	Display Size	254
	Precision	1073741824	Precision	254
	Scale	0	Scale	0



Column Name	Version 1.x		Version 2.x	
SOURCE_DATA_TYPE	Metadata	Value	Metadata	Value
	Type Name	smallint	Type Name	INTEGER
	Type ID	5	Type ID	4
	Display Size	6	Display Size	11
	Precision	5	Precision	10
	Scale	0	Scale	0

## getSchemas

Column Name	Version 1.x		Version 2.x	
TABLE_SCHEM TABLE_CATALOG	Metadata	Value	Metadata	Value
	Type Name	varchar	Type Name	VARCHAR
	Type ID	-16	Type ID	12
	Display Size	1073741824	Display Size	128
	Precision	1073741824	Precision	128
	Scale	0	Scale	0

## getTables

Column Name	Version 1.x		Version 2.x	
TABLE_CAT TABLE_SCHEM TABLE_NAME TABLE_TYPE TYPE_CAT TYPE_SCHEM TYPE_NAME SELF_ REFERENCING_ COL_NAME REF_ GENERATION	Metadata	Value	Metadata	Value
	Type Name	varchar	Type Name	VARCHAR
	Type ID	-16	Type ID	12
	Display Size	1073741824	Display Size	128
	Precision	1073741824	Precision	128
	Scale	0	Scale	0
REMARKS	Metadata	Value	Metadata	Value
	Type Name	varchar	Type Name	VARCHAR
	Type ID	-16	Type ID	12
	Display Size	1073741824	Display Size	254
	Precision	1073741824	Precision	254
	Scale	0	Scale	0

## Data Type for TIME Literal in Query Result

For a query such as `SELECT TIME '12:00:00'`, the connectors use different data types in the query result set for the TIME literal column.

Version 1.x	Version 2.x
TIME	VARCHAR

## Upgrading from 2.0.2 to 2.0.5 or later

### Result Set Streaming Support

Starting with version 2.0.5, the connector uses the result set streaming API to improve the performance in fetching query results. To take advantage of this feature, you must do the following:

- Include and allow the `athena:GetQueryResultsStream` action in your IAM policy statement. For details on managing Athena IAM policies, see <https://docs.aws.amazon.com/athena/latest/ug/access.html>.
- If you are connecting to Athena through a proxy server, make sure that the proxy server does not block port 444. The result set streaming API uses port 444 on the Athena server for outbound communications.